

Datasheet

SMB SOLAR-MULTIBOARD - a light, slip-resistant and mobile working platform, which allows working (maintenance, cleaning, repair) on PV modules with frames. No damages to PV modules will occur if applied properly and according to the instructions of the manual.

Specifications:

Frame:

Aluminum with slip-resistant surface

Protective layer:

UV resistant PE (poly ethylene), glued and mounted

Flaps:

Aluminum incl. vulcanized rubber layer, wall thickness 6 mm, insertion depth between modules 55 mm +/- 5 mm

Handgrip:

Centered at the lower end of the board, width 150 mm +/- 3 mm, height 30 mm +/- 2 mm

Manual:

Colored manual in C6 format, enclosed in a transparent envelope and stuck into the opening of the handgrip for removal

Load capacity:

Not to exceed 150 kilogram - only one person allowed

Roof inclination:

Acc. to DIN 51 130 the total mean of inclination angle may exceed 40° (R13 V10)



	SMB Solar-Multiboard 1080 mm	SMB Solar-Multiboard 1780 mm	SMB Solar-Multiboard 2040 mm
Order- No.	SMB 1080-400	SMB 1780/400	SMB 2040/400
Length	1080 mm +/- 10mm	1780 mm +/- 10mm	2040 mm +/- 10mm
Width	400 mm +/- 5mm	400 mm +/- 5mm	400 mm +/- 5mm
Height	60 mm +/- 3mm	60 mm +/- 3mm	60 mm +/- 3mm
Weight	6,00 kg +/- 0,1 kg	10,00 kg +/- 0,1 kg	12,00 kg +/- 0,1 kg

The description of the products, their application, possibilities and performance data are no guaranteed characteristics and subject to technical alterations | April 2014

SMB SOLAR-MULTIBOARD GmbH

Oberstr. 7 | D-52388 Nörvenich | Germany

www.solar-multiboard.de | info@solar-multiboard.de

Tel.: +49 24 26 - 95 87 90 | Fax: +49 24 26 - 95 88 60 | Mobile: +49 1 60 827 82 44